



**Bureau de normalisation
du Québec**

BNQ is a member of the National
Standards System (NSS).

ANNEX TO THE CERTIFICATE

SUBOR BORU SAN. TIC. A.S.

Page 1 of 2

Plant. Ahrneller Mal Sehit Mustafa Geyve Cad. Nu. 45
Karapürçek, Sakarya 54430
Turkey

ASTM D3262/2020-03-01

Fiberglass (Glass-Fiber-Reinforced Thermosetting-Resin) Sewer Pipe

Numéro du certificat : **4362**
Date de délivrance : **2026-03-11**
Date d'expiration : **2027-03-31**

DESCRIPTION			
Pipe Designation Code: ASTM D3262-1-1-1-C, see note 1 below			
Nominal Pipe Size (mm)	Nominal Pipe Size (mm)	Nominal pressure, psi (bar)	Pipe Stiffness, psi (kPa)
DN, Ductile Iron Pipe Eq.	DN, international O.D.	PN 14,5 (1)	SN 36 (248)
250	-	Certified	Certified
300	-	Certified	Certified
400	-	Certified	Certified
450	-	Certified	Certified
-	800	Certified	Certified
-	1000	Certified	Certified
-	1100	Certified	Certified
-	1200	Certified	Certified
-	1300	Certified	Certified
-	1400	Certified	Certified
-	1500	Certified	Certified
-	1600	Certified	Certified
-	1700	Certified	Certified
-	1900	Certified	Certified
-	2200	Certified	Certified
-	2300	Certified	Certified
-	2800	Certified	Certified
-	3000	Certified	Certified
-	3200	Certified	Certified
-	3400	Certified	Certified
-	3800	Certified	Certified

Note 1: Joint Tightness has been verified with GRP REKA type flexible joint-double bell sewer coupler (Unrestrained Coupling Joints) for a maximum nominal working pressure of 14,5 psi. The Pipe trademark is SUBOR.

THE ANNEX IS AN INTEGRAL PART OF THE CERTIFICATE.



Bureau de normalisation
du Québec

BNQ is a member of the National
Standards System (NSS).

ANNEX TO THE CERTIFICATE

SUBOR BORU SAN. TIC. A.S.

Page 2 of 2

Plant. Ahrneller Mal Sehit Mustafa Geyve Cad. Nu. 45
Karapürçek, Sakarya 54430
Turkey

ASTM D3262/2020-03-01*Fiberglass (Glass-Fiber-Reinforced Thermosetting-Resin) Sewer Pipe*Numéro du certificat : **4362**Date de délivrance : **2026-03-11**Date d'expiration : **2027-03-31****HISTORY**

Date	Description
2025-03-24	Issuance of certificate.
2026-03-11	Modification of certificate: add DN400 mm, PN14,5 psi, SN36.

THE ANNEX IS AN INTEGRAL PART OF THE CERTIFICATE.